

based on Hungarian Government Ordinance 275/2013 (VII. 16.) of the detailed regulations on designing and applying construction products into buildings and their proofing of performance.

Declaration ID: TNY\_Thermomaster.Universal.primers-20150701\_EN

*Manufacturer, retailer of construction product:*

Masterplast Kft. - H-8143 Sárszentmihály, Árpád u. 1/A. (Tel: +36-22/801-300, Fax: +36-22/801-382)  
Email: [masterplast@masterplast.hu](mailto:masterplast@masterplast.hu); Web: [www.masterplastgroup.com](http://www.masterplastgroup.com)

*Name of product:*

Thermomaster Universal Primer.

*The performance consistency evaluation and inspection system for the construction product (according to the system(s) listed in Annex V of the Regulation (EU) 305/2011 of the European Parliament and Council):*

4

*The reference number and date of issue of the standard, national technical approval or ÉME technical approval used for basic characteristics evaluation:*

-

*Designation and designed application method of construction product:*

Primer for wall surfaces before the application of acrylic, silicone or silicate decorative render finishes. As a key-coat, it equalises the water absorption of the surface and increases its water repellency; it extends the processing time of the applied render and improves the adhesion to very smooth surfaces.

Basic characteristics	Related standard	Performance	Tolerance	Performance class
Density		1,2 kg/dm <sup>3</sup>		
Temperature conditions - surface and air (R.h. < 80%, protected against sun, wind and rainfall with curtains)		between (+)5 °C - (+)35 °C (do not work in rain, fog or strong wind (≥30 km/h) despite such protection.)		
Consumption (one-layer application, depending on the water absorption and roughness of the surface)		0,12 – 0,2 l/m <sup>2</sup> 0,14 - 0,24 kg/m <sup>2</sup>		
Dilution		max 5% (with clear water)		
Drying time (+20 °C, r. h. 65 %)		~ 2 hours (touch dry); ~ 12 hours (suitable for the next layer)		
Resistance to precipitation (washing away of the application) (+20 °C, r. h. 65 %)		~ 24 hours		
Volatile organic content (VOC)		< 2 g/l	EU VOC requirement – A/g: < 30	

*Other information:*

Guidelines regarding the planning (Hungarian Building Chemistry- and Plaster Association – MÉSZ, 2012) and application (MÉSZ, 2014) of external thermal insulation systems (ETICS).  
TD\_Thermomaster.Universal.primers-20150701\_EN

*Declaration of Performance validity:*

Valid for products sold by Masterplast Kft. until the product's life expectancy or until the modification or withdrawal of the Declaration. The modified version of this Declaration invalidates previously issued Declarations. The current version of the Declaration can be accessed under [www.masterplastgroup.com](http://www.masterplastgroup.com).

Sárszentmihály, 01<sup>st</sup> of July, 2015

 **MASTERPLAST KFT.**  
8143 Sárszentmihály, Arpád u. 1/A.  
Adószám: 14025477-4-07  
Csoportos Adószám: 17780151-5-44  
Raiffeisen: 12023008-00159007-00100001



Csokló Gábor  
Regional Production Manager,  
Manager for Innovation and Technology

Complaints regarding the product are accepted only with a proof of purchase (bill, waybill) issued by Masterplast Kft. for the purchased amount and provided the product can be identified.