

ChovACUSTIC® 65 FIELTEX

CÓD. 56303

DESCRIPTION

Multilayer compound formed by a textile felt of 16 mm. thermally adhered to a high density sheet of 4 mm.

Excellent and versatile device to reduce the air noise transmission in a wide frequency range, thanks to:

- High density and elasticity (viscoelastic sheet).
- High-porosity (textile felt).



INSTALLATION

- 1- Cut a section of **ChovACUSTIC®** taking into account the partition dimension. To do this, use a cutter or a radial saw.
- 2- Support the **ChovACUSTIC FIELTEX** on the partition. Make holes on the material with a drill and 8mm. bits.
- 3- Making 5 holes per square metre.
- 4- Depth should be at least 4cm.
- 5- Introduce the fixing pins ChovAFIX 6 with a hammer aid.
- 6- Repeat these steps, taking into account the overlap of the sheets.
- 7- Put **ChovASEAL** adhesive sealing tape at all joints of the sections to ensure a seal.



ChovACUSTIC® 65 FIELTEX

TECHNICAL SPECIFICATIONS

THICKNESS (mm)	20
AVERAGE WEIGHT (kg/m ²)	7,4
THERMAL CONDUCTIVITY (W/m·K)	0,032
REACTION TO FIRE	F
SOUNDPROOFING IN DOWNSPOUTS (R;dBA)	57*
DIMENSIONS (m)	5,5 x 1
m ² / PALLET	66
STORAGE: The material must be kept from weather and stored upright.	

* Theorist calculation.

RECOMMENDED FOR...

- Acoustic treatments in activity establishments, as bars, restaurants, clubs...
- Reinforcement in traditional building materials soundproofing such as dividing in a single brick piece.
- Reduced thickness solutions in rehabilitation.
- Machine rooms and buildings common areas.